



3LCD Lightweight Standard Throw Laser Projector For Gaming 5200lm

Basic Information

Brand Name: YeoanModel Number: YA-526U

• Minimum Order Quantity: 5

• Packaging Details: Packaging Box Dimensions (WxDxH mm):

492*443*239

• Delivery Time: 15 days

• Payment Terms: L/C, T/T, Western Union



Product Specification

Brightness: 5200lm Mkt
Projection Light Source: Laser
Display Technology: 3LCD
Projection Size: 30-300"
Projection Ratio: 1.37~1.65 1

• Aspect Ratio: Native:16:10 Compatible: 4:3/16:9

• Focus Mode: Manual

Keystone Correction: V: ±30° H ±30° 4 Corner
 Resolutioin: WUXGA 1920×1200

• Highlight: lightweight Standard Throw Laser Projector,

3LCD Standard Throw Laser Projector, lightweight laser projector for gaming

Product Description

Advanced, 3-Chip, 3LCD Design — 3LCD technology ensures no color wheel, no white segment and no rainbow effect

HDR10 (2) High Dynamic Range and Rich Black Contrast — full 10-bit color output and a contrast ratio up to 5000,000:1 deliver an extraordinary range of color and detail in both bright and dark scenes.

100% Balanced Color Brightness — 2,200 lumens of equal color and white brightness (4) for vibrant, rich color, even in rooms with ambient light

Highlights: Fashion design and light weight, WUXGA(1920×1200)

3LCD display, Laser light source, 5600 ISO Im high light

1.2X, 1.6X and 1.66X zoom lenses 30,000H light source life

5,000,000:1 dynamic contrast ratio

Application:

Widely used at home, classroom, office, meeting room, hotel, hospital, school, church, factories and son on.

Key parts		
	Panel	SONY 0.63"
	Throw Ratio	1.37~1.65:1
	Zoom Ratio	1.2X Zoom
	Lens Shift	N/A
	Light source	LASER
	Resolution	WUXGA(1920×1200)
Brightness	1 10001011011	11071071(102071200)
nighth ood	BrightnessMKT	5200
ISO21118	BrightnessTYP	4680
	Brightness MIN	4160
Vierell Cons	Brightness Willy	4100
Overall Spec	E 1181 1/81 1	000001
	FullNormal/Normal mode	20000hrs
ight source Life time	ECO1 mode	30000hrs
	ECO2 mode	30000hrs
Projection Lens	F	1.6~1.76
	f	19.158~23.018mm
	Zoom/Focus	Manual
	Throw Ratio	1.37~1.65:1
	Zoom Ratio	1.2x optics
	Screen size	30-300 inch
	Lens Shift	N/A
	Dynamic Contrast Ratio	
_	(FOFO)	5000,000:1
CR	Native Contrast Ratio	
	(FOFO)	400:1(Min)
	<u> </u>	37dB(Normal) 30dB(ECO1)
loise	Noise(dB)	28dB(ECO2)
	Uniformity(Actual Min)	2002(2002)
Iniformity	-ISO21118	80%
AR	Aspect Ratio	Native:4:3 Compatible: 16:9/16:10
erminal(I/O port)	Aspect Hatio	Native:4.3 Compatible: 10.9/10.10
emmai(i/O port)	VGA	*1
		*2
	HDMI	
	Video	*1
	Audio in	*1
	(mini jack,3.5mm)	
	Audio in (RCA×2) <audio< td=""><td></td></audio<>	
Input	L/R>	*1
	USB-A	*1
	USB-B	*1(Display)
	RJ45	*1(Display)
		N/A
	YCbCr/Component	
	S-Video	N/A
Output	VGA	*1
	Audio out	*1
	(mini-jack,3.5mm)	
Control	RS232	*1
JOHE OF	RJ45	*1 (Control)
	Other Interface	N/A
eneral Spec		
	Speaker	16W*1
udio		1
		IW/Filter
Oust filter		W/Filter
Audio Dust filter Filter Life time	Power Poqueiromente	7000h
Oust filter	Power Requeirements Power Consumption	

Power Consumption	Power Consumption (ECO1) (Max)	175
	Power Consumption (ECO2) (Max)	160
	ECO Standby Mode Power	<0.5W
	Consumption	0: 40 ! 0
	Operating Temp.	0 to 40deg.C
	Operating Thumidity.	20-80%
Temp.&Humidity	Storage Temp.	'-10 to 50deg.C
	Storage Thumidity.	10-85%
	High altitude	0-3000m
Other Functions		
	Keystone Correction	V: ±30° H:±30°
Keystone	(Lens@center)	4 corner
OSD	Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese,Thai, Farsi
	LAN Control-RoomView	Voc
	(Crestron)	Yes
LAN Control	LAN Control	
	AMX Discovery	Yes
	LAN Control	
	PJ Link	Yes
		15100KH-
Scanning Frequency	H-Synch Range	15~100KHz
	V-Synch Range	24~85Hz
Display Resolution	Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,4K @30Hz
	Video Signal Input	480i, 480p, 576i, 576p, 720p, 1080i and 1080p
SW setting	Auto Setup	INPUT SEARCH,AUTO PC,Auto Keystone
	Blank	Yes
	Suspend	Yes(5miniutes no singnal as default
		Dynamic,Standard,Cinema,
	Picture mode	Colorboard, Blackboard (Green)
	Cooling time	5s
		1
	Closed caption	Yes
	Auto Ceiling	Yes
	D-Zoom	1~19
	360° projection	Yes
Others	Wireless display (Optional function)	SmartPhone: Android:Install APK for Android iphone: Airplay function PC: Support WiFi Display@Windows&MAC system
Dimensis (OM/-1-1-1		through dongle
Dimension&Weight	MAN D:	
	MAX Dimensions	390*294*128
	(WxDxH mm)	
	Net. Weight (KG)	5Kg
	Packaging Box Dimensions	492*443*239
	(WxDxH mm)	492 443 239
		~6.5Kg
Accessory	(WxDxH mm)	
Accessory	(WxDxH mm) Gross. Weight (KG)	~6.5Kg
Accessory	(WxDxH mm)	~6.5Kg Chinese,English Power cord Remote control&RC
	(WxDxH mm) Gross. Weight (KG) Manual Languages	~6.5Kg Chinese,English
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC FDA	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Accessory Regulation List WW US	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC FDA	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List WW	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC FDA CE-EMC	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List WW US	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC FDA CE-EMC CE-LVD CE-ERP	~6.5Kg Chinese,English Power cord Remote control&RC Battery
Regulation List WW	(WxDxH mm) Gross. Weight (KG) Manual Languages Standard Accessaries CB cTUVus FCC FDA CE-EMC CE-LVD	~6.5Kg Chinese,English Power cord Remote control&RC Battery V V V V V V V V V V V V V



Hefei Yeoan Information And Technology Co.,Ltd.

+8613866663080

zero@yeoan.com

projector-hd.com

No. 79 Kexue Avenue, Keyuan Pioneer Center, High-tech Zone, Hefei City, Anhui Province.