



3600lm Ultra Short Throw Laser Projector 4k For Home Theater OEM

Basic Information

Brand Name: YeoanModel Number: YA365Minimum Order Quantity: 5

• Packaging Details: packing size: 470*410*166mm

• Delivery Time: 15 days

• Payment Terms: L/C, T/T, Western Union



Product Specification

Brightness: 3600lm
Display Technology: 3LCD
Projection Light Source: Laser
Standard Resolution: 1280 X 800
Projection Ratio: TR 0.254:1

• Aspect Ratio: Native:16:10 Compatible: 4:3/16:9

• Focus Mode: Manual

Keystone Correction: Auto, Vertical And Horizontal

• Highlight: 3600lm short throw laser projector 4k,

OEM short throw laser projector $4k\,,$

OEM ultra 4k projector

Product Description

This Ultra short throw projector offers an exceptional home entertainment experience with sharper images and seamless compatibility with smart home devices. It's a deluxe ultra short throw projector table made for those who love an immersive home theater experience. It brings together advanced technology, great features, and a stylish vibe that takes your viewing experience to new heights.

Highlights:

3LCD projection technology

Fashion design and light weight, ultra short throw 0.254:1

Resolution 1280 x 800, 3600 lumen brightness,

Latest system, Auto keystone correction, Wireless screen sharing,

HDMI port, 2.4G/5G WIFI, Silent fan, 360° projection,

Application:

Widely used at home, classroom, office, meeting room, hotel, hospital, school, church, factories and son on.

	Brightness (Anti Lumen)	3600
	Resolution	1280 × 800
Key parts		
	Panel	SONY 0.64"
	Throw Ratio	0.254:1
	Zoom Ratio	N/A
	Lens Shift	N/A
	Light source	LASER
Overall Spec		
	FullNirmal/Normal mode	20000hrs
Light source Life time	ECO1 mode	30000hrs(TBD)
	ECO2 mode	TBD
	F	1.7
	f	2.94mm
	Zoom/Focus	Manual
Projection Lens	Throw Ratio	0.254:1
	Zoom Ratio	N/A
	Screen size	80-120 inch
	Lens Shift	N/A
CR	Dynamic Contrast Ratio (FOFO)	5000,000:1
	Native Contrast Ratio (FOFO)	350:1(Min)
Noise	Noise(dB)	TGT: 37dB(Normal) 27dB(ECO1)
Uniformity	Uniformity(Actual Min) -ISO21118	80%
AR	Aspect Ratio	Native:16:10 Compatible: 4:3/16:9
Terminal(I/O port)		
	VGA	*1
	HDMI	*2
	Video	*1

1		
	Audio in (mini jack,3.5mm)	*1
Input	Audio in (RCA×2) <audio L/R></audio 	*1
	USB-A	*1
	USB-B	*1(Display)
	RJ45	*1(Display)
	YCbCr/Component	N/A
	S-Video	N/A
Output	VGA	*1
	Audio out (mini-jack,3.5mm)	*1
	RS232	*1
	RJ45	*1 (Control)
Control	USB-B	*1
	LAN	*1
General Spec		
Audio	Speaker	16W*1
Dust filter		W/Filter
Filter Life time		7300h(TBD)
	Power Requeirements	100~240V@ 50/60Hz
Power Consumption	Power Consumption (Normal) (Max)	TBD
	Power Consumption (ECO1) (Max)	TBD
	Power Consumption (ECO2) (Max)	TBD
	ECO Standby Mode Power Consumption	<0.5W
	Operating Temp.	5 to 40°C
	Operating Thumidity.	20-80%
Temp.&Humidity	Storage Temp.	-10 to 50°C
	Storage Thumidity.	10-85%
	High altitude	1700-3000m
Other Functions		
Keystone	Keystone Correction (Lens@center)	V: ±15° H: ±15° Pincushion/Barrel Correction 4 corner 6 Corner Geometry correction Grid image tune
OSD	Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch ,Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak,Vietnamese,Thai, Farsi
LAN Control	LAN Control-RoomView (Crestron)	Yes
	LAN Control AMX Discovery	Yes
	LAN Control PJ Link	Yes
Scanning Frequency	H-Synch Range	15~100KHz
	V-Synch Range	24~85Hz

Display Book Vo.	Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA,4K@30Hz
Display Resolution	Video Signal Input	480i, 480p, 576i, 576p, 720p, 1080i and 1080p
	Auto Setup	INPUT SEARCH,AUTO PC,Auto Keystone
	Blank	Yes
	Suspend	Yes(5miniutes no singnal as default)
SW setting	Picture mode	Dynamic, Standard, Cinema, Colorboard, Blackboard(Green)
	Cooling time	5s
	Closed caption	Yes
	Auto Ceiling	Yes
	D-Zoom	1~19
	360° projection	Yes
Others	Wireless display (Optional function)	SmartPhone: Android:Install APK for Android iphone: Airplay function PC: Support WiFi Display@Windows&MAC system through dongle
Dimension&Weight		
	MAX Dimensions (WxDxH mm)	470*410*166; With lens protrusion
	Net. Weight (KG)	9Kg
Accessory		
	Manual Languages	Chinese,English
	Standard Accessaries	Power cord Remote control&RC Battery





Hefei Yeoan Information And Technology Co.,Ltd.









