



IP65 dust-proof 1080p DLP Large Venue Projectors Electric Zoom And Focus 1920x1200

Our Product Introduction

Basic Information

- Brand Name: Yeoan
- Model Number: FH1755B
- Minimum Order Quantity: 1
- Packaging Details: talked with me to get the details
- Delivery Time: 15 days
- Payment Terms: L/C, T/T, Western Union



Product Specification

- Light Luminance: 15500 Lumens
- Feature: Support High Altitude
- Projection Light Source: Laser
- Display Technology: DLP
- Standard Resolution: WUXGA (1920x1200)
- Throw Ratio: 1.2~2.0: 1
- Lens Shift Range: Vertical: $\pm 100\%$ horizontal: $\pm 30\%$
- Focus Mode: Electric Motorized
- Keystone Correction: Automatic, Vertical: ± 30 Degrees Horizontal: ± 30 Degrees
- Projection Mode: 360° Projection
- Highlight: **IP65 waterproof Large Venue Projectors, 1920x1200 Large Venue Projectors, waterproof 1080p dlp projector**

for more products please visit us on projector-hd.com

Product Description

Highlights:

- Long-life laser light source (25,000 hours in green mode)
- Sealed light source (IP65) to prevent dust intrusion, avoid dust causing brightness loss and color unevenness
- Sealed internal circulation intelligent cooling system with built-in independent cooling system, TEC + air cooling technology
- HDMI, DVI, 3D Sync, VGA input supports 120Hz 3D
- With vertical and horizontal keystone correction and four-corner correction functions
- Standard support for HDBaseT long-distance network transmission function
- Support horizontal and vertical 360° rotation installation
- Support Crestron, P-Link
- **Support high altitude mode (below 5000Meters)**
- Quick power on and off function, power off protection function
- Electric zoom, electric focus
- Extreme color technology (DLP™)
- Can be used in an environment with a temperature of 5°C-35°C

| | FH1733B | FH1755B |
|----------------------------------|--|---------|
| Chip size | DLP(0.67"DM D) | |
| Physical resolution | WUXGA (1920x1200) | |
| Brightness (lumens* 2) | 13300 | 15500 |
| Uniformity* 2 | 90% | |
| Contrast* 2 | 1,500:1 Static 30,000:1 Extreme Black | |
| Light source life | 20000H, Green Mode 25000H | |
| Throw ratio (standard mirror) | 1.22-1.53 / 1.2-2.0 | |
| Alternative lenses | 0.31-0.36 / 0.61-0.71 / 0.51-0.65 / 0.65-0.76 / 0.75-0.95 / 0.95-1.22 / 1.52-2.92 / 2.9-5.5 / 5.5-9.3 | |
| Focus Circle | 70~400 inch | |
| Zoom/focus mode | Manual/electric zoom | |
| Range of movement | about : 60% up and down: 100% | |
| Color Space | 110% REC709 | |
| Keystone Correction | Level: Earth 25° vertical : earth 30° | |
| Aspect Ratio | 16 : 10 (4:3 , 16:9 , 16 : 10 , 16:6) | |
| Cooling method | TEC +Liquid cooling +Air cooling technology | |
| Projection method | Front projection / rear projection / desktop / ceiling mount | |
| Power consumption | Working power : 1250W +/-10% , Standby power consumption : 0.5W | |
| Menu language | Chinese, English, Traditional Chinese | |
| Product noise | Normal : 45dB, Eco: 36DB | |
| Operating altitude | 4000M the following | |
| Operating temperature | 5-35° | |
| Storage temperature | 20°C arrive 60°C | |
| net weight | 35KG | |
| Dimensions (width x high x deep) | 525mm*580mm*244mm (without lens) | |
| Signal interface | VGA IN/OUT X1, DVI X1, HDMI X2, HDBASET X1, S-video X1, USB : X1(Out : 5V/ 1.5A(M AX)) Video X1, Audio IN/ Out X1, BNC: X5(Format:RGBHV/YPBPR/YCBCR), AC IN X1 | |
| Control interface | 3D SYNC X1, Mini USB X1(Download FW), RS232 input/Output X1, LAN control (RJ45) X1 | |



Hefei Yeoan Information And Technology Co.,Ltd.



+8613866663080



zero@yeoan.com



projector-hd.com

No. 79 Kexue Avenue, Keyuan Pioneer Center, High-tech Zone, Hefei City, Anhui Province.

