



65inch Wall Mounted Advertising Display 8G For Loop Playback Split Screen

Basic Information

- Brand Name:
- Model Number:
- YEOAN BG490-65 50

30days

L/C, T/T

- Packaging Details: Packing carton: 1550*970*150 mm
- Delivery Time:

• Minimum Order Quantity:

• Payment Terms:



Product Specification

- Mounting Type:
- Power Supply: • Viewing Angle:
- Wall Mounted AC
- 178
- Response Time:
- · Contrast Ratio:
- Resolution:
- Screen Size:
- Display Type:
- Brightness:
- Touch Screen:
- Connectivity:
- Operating System:
- Language Menu:
- Metal Shape:
- Frame Colour:

| AC 100-240V, 50/60Hz | |
|-----------------------|--|
| 178° | |
| 8 Ms | |
| 1200:1 | |
| 1920x1080 | |
| 65 Inch | |
| LCD | |
| 350 Cd/m ² | |
| Yes | |
| HDMI, VGA, USB | |
| Android Or Windows | |

- English, Chinese And Other Languages
- Can Be Customized
- Can Be Customized



1 horizontal install





(3) ceiling install

(4) standby

Our Product Introduction

Product Description

Feature:

- 1: BG series products adopt new environmental protection technology, high stability, can adapt to and work normally in harsh environments
- 2: Professional industrial LCD screen, video images are clearer, natural, delicate, and visually more impactful.
- 3: Ultra-thin design concept, thickness is only 18mm, stylish and generous appearance.
- 4: With automatic adjustment function to enhance the image layering
- 5: With automatic elimination of residual image function to protect the long-term use of LCD screen
- 6: High resolution, high contrast, high brightness, greatly improve the picture layering, can better show details.
- 7: With an ultra-long service life of more than 60,000 hours, and can work 7*24 hours uninterruptedly

Playback method

Insert the U disk/SD card with pictures, videos and other materials into the advertising machine, and automatically play in a loop

Function display

Equipped with 8G SD card storage, the vertical screen source cannot be automatically converted, and needs to be converted to split screen playback through computer software. Vertical screen and split screen playback need to be made. It is recommended to use the smart stand-alone version.

Image format:

JPG/PNG/BMP (color mode is RGB Video format: AVL MP4, MPG, MOV, etc. [Speed 25-30FPS or less, video code stream supports a maximum of 20M/S] Music format: MP3, WM4

Smart catering wall-mounted advertising machine can realize the interaction between restaurant operators and consumers. The catering multimedia publishing system can place advertising machines in various places such as hall stairwells and boxes to play catering introductions, local tourism, time, weather and other information, and support different locations to play different information. The integrated cold rolling process of metal stamping, the matching of theprofile frame, and the high-transmittance tempered glass have a grand and stable appearance and are widely used in business, administration, education, entertainment and other fields.

| size | 50" | 55" | <mark>65"</mark> |
|---------------------------------|--|---|-----------------------------|
| Display parameters | | | |
| Panel size | 50" | 55" | 65" |
| Resolution | 1920*1080(pixels) | 1920*1080(pixels) | 1920*1080(pixels) |
| Pixel pitch | 0.28* 0.28 mm | 0.63* 0.63mm | 0.37*0.37mm |
| brightness | 350cd/m ² (typ.) | 350cd/m² (typ.) | 350cd/m ² (typ.) |
| Contrast | 1200:1 (typ.) | 1200:1 (typ.) | 1200:1 (typ.) |
| Color | 16.7M (8bit) | 16.7M (8bit) | 16.7M (8bit) |
| Response time | 8ms (typ.) | 8ms (typ.) | 8ms (typ.) |
| Viewing area (H*V) | 1095.8*616.4 mm | 1209*680 mm | 1428.5×803.5mm |
| Angle (H*V) | 178°/178° | 178°/178° | 178°/178° |
| Service life | 30,000 hrs (typ.) | 30,000 hrs (typ.) | 30,000 hrs (typ.) |
| Mainboard parameters (optional) | V100 motherboard (4K solution) | Windows motherboard (2K solution) | |
| Running the system | Android 12 | Win 7/Win 10 | |
| chip | GK6760- V100Octa-core cortex A55Frequency1.5 GHz | I5-3210MDual-core four-thread main frequency 2.5GHz | |
| Memory | 2G | 4G | |
| storage | 16G | 128G | |
| network | 100MEthernet/Wi Fi-2.4G | 100M/1000MEther net/WiFi-2.4G | |
| Video Format | supportAVS,HDC P,mp4,H264,H26 5wait | MPEG2- 4,H.264wait | |
| Image Format | JPG, JPEG, BMP, PNG,wait | JPG, JPEG, BMP, PNG,wait | |
| Menu language | Chinese/English, etc. | Chinese/English, etc. | |
| External connection port | | | |
| USB2.0 | *1(support1roadU SB 3.0) | *2(support2路USB 3.0) | |
| USB2.0(OTG) | *1 | *2 | |
| HDMIinterface | *1(supportHDMle nter) | *1(supportHDMIOu tput) | |
| RJ45 | *1 | *1 | |
| WIFI 2.4Gantenna | *1 | *1 | |
| Touch parameters | | | |
| Touch Type | Infrared touch | Infrared touch | Infrared touch |

| Touch points | 10point | 10point | 10point |
|---|---|--|---|
| power supply | | | |
| Speaker power | 5W*2 | 5W*2 | 5W*2 |
| Standby power | ≤0.5W | ≤0.5W | ≤0.5W |
| Power supply for the whole machine | AC110V- 220V,50-60 Hz | AC110V-220V,50- 60 Hz | AC110V-220V,50-60 Hz |
| Machine power | ≤120W | ≤150W | ≤180W |
| Work Environment | | [| |
| Operating temperature | 0 ~40 | 0 ~40 | 0 ~40 |
| Operating humidity | 20%~85%(No condensation) | 20%~85%(No condensation) | 20%~85%(No condensation) |
| Storage temperature | -10 60 | -10 60 | -10 60 |
| Storage humidity | 10%~ 60%(No condensation) | 10%~ 60%(No condensation) | 10%~ 60%(No condensation) |
| Material | | | |
| Housing Material | Aluminum frame + tempered glass + metal back cover | Aluminum frame + tempered glass + metal back cover | Aluminum frame + tempered glass + metal back cover |
| Shell color | Silver + black frame + black back cover | Silver + black frame + black back cover | Silver + black frame + black back cover |
| size | | | |
| Bare metal size (W*H*D) | 1134.2*655.4*67. 3 mm | 1251.7*723.4*66.9 mm | 1467*845*65.3 mm |
| External dimensions of packaging (W*H*D) | 1230*770*150 mm | 1340*850*150 mm | 1550*970*150 mm |
| VESAhole | 400*400mm, 4*M8screw | 400*400mm, 4*M8screw | 400*400mm, 4*M8screw |
| weight | | | |
| net weight | 22KG | 26KG | 40KG |
| Gross Weight | 25KG | 29KG | 43KG |
| appendix | | | |
| Power cord | *1 | *1 | *1 |
| Warranty card | *1 | *1 | *1 |
| Certificate | *1 | *1 | *1 |
| Wall Mount | *1 | *1 | *1 |
| Dimensions | | 1 | |





Multiple function split screen wifi remote control V & H install super config. recycling 4K Touchable on/off scheduled **4**K



No. 79 Kexue Avenue, Keyuan Pioneer Center, High-tech Zone, Hefei City, Anhui Province.