



# DLP Projector For Large Rooms Lecture Hall 500 Inch Huge Screen Optional Lens

## **Basic Information**

Brand Name: Yeoan
Model Number: YAC801
Minimum Order Quantity: 5

Packaging Details: Packaging Box Dimensions (WxDxH mm):

574 W)\*554(D)\*268(H)

Delivery Time: 15 days

Payment Terms:
 L/C, T/T, Western Union



# **Product Specification**

• Brightness: 8000lm

Standard Resolution: 1080P (1920 X 1080)
 Display Technology: DLP 0.65dmd
 Projection Light Source: Laser Light Source

Projection Screen: 60-500"
Lens Optional: Yes
Standard Lens Ratio: 1.17~1.88 1
Contrast Ratio: 5,000,000:1

• Aspect Ratio: Native:16:9 Compatible: 4:3/16:10

Keystone Correction: V ±30° 4 Corner Correction
 Lens Shift: V: 50% 10% H:±8%

• Zoom Ratio: 1.6x Manual

• Highlight: DLP Projector For Large Rooms,

Lecture Hall DLP Projector



# **Product Description**

### Highlights:

Outfit complex installations with 1080P, 8000 lumens professional installation projector engineered for large meeting rooms, auditoriums, museums, houses of worship and broadcast environments. laser light source features an IP5X-certified optical engine for up to 30,000 hours (Eco) of maintenance-free light source life. Integrated image warping, blending, four corner adjustment and lens position memory simplify complex installations.

### Optional five lens from standard long throw to short throw

#### Application

Widely used at large venue for home, classroom, office, meeting room, hotel, hospital, school, church, factories and so on.

	Resolution	1080P
	Model#	YAC801
Key parts		
	Throw Ratio	1.17(wide)-1.88(tele)standard lens
	Zoom Ratio	1.6x
		I .
2:11	Light source	LASER
Brightness		
	BrightnessMKT (TBD)	8000
	BrightnessTYP (TBD)	7200
	BrightnessMIN	6400
Overall Spec		
1	Display Panel	0.65" DMD
	Display Technology	DLP
	Native Resolution	1080P (1920 x 1080)
Light source Life	Full Normal/Normal	20000hrs
	mode	
	ECO1 mode	30000hrs
	ECO2 mode	NA
	F	2.4
	f	17.2~27.7mm
	Zoom/Focus	Manual
Projection Lens	Throw Ratio	1.17 <sub>(</sub> wide)-1.88 <sub>(</sub> tele <sub>)</sub>
-rojection Lens		
	Zoom Ratio	1.6
	Screen size	60-500 inch
	Lens Shift	V: 50% -10%, H:±8%
CR	Contrast Ratio (FOFO)	5000000:1
Noise	Noise(dB)	39dB(Normal) 36dB(ECO)
Uniformity	Uniformity(Actual Min) -JISX6911	95%
AR	Aspect Ratio	Native:16:9 Compatible: 4:3/16:10
Terminal(I/O port)	·	·
ai(" > poit)	VGA	*2
Input	HDMI 1.4B(IN)	*2
	USB-A	N/A
	USB-B	N/A
	I	
	RJ45	N/A
	DVI-D	N/A
	HD BaseT	*1(Optional)
	HD-SDI(3G-SDI)	N/A
	Video	*1
	Audio L (RCA)	*1
	Audio R (RCA)	*1
	Audio in	
	mini jack,3.5mm	*1
	VGA	*1
Output	HDMI 1.4B(OUT)	N/A
	Audio out	10/17
	MUUIO OIII	*1

RS232	*1
RJ45	*1 (Control)
USB-B	*1 (For upgrade)
USB (Type A) only support 5V	*1
Wired Remote(OUT)	N/A
Speaker	10W*1
	NA
	NA
Power Requeirements	100~240V@ 50/60Hz
(Normal) (Max)	670
(ECO1) (Max)	520
(ECO2) (Max)	NA
ECO Standby Mode Power Consumption	<0.5W
Operating Temp	0m≤Altitude≤1700m <sub>,</sub> Ambient0 ~50
Operating remp.	1700m Altitude 3000m, Ambient 0 ~40
Operating Thumidity.	20-85%
Store Temp.	f-10 to 50deg.C
High altitude	0~3000m
Keystone Correction	V:±30°
(Lens@center)	4 Corner Correction
Languages	26 languages: English, German, French, Italian, Spanish, Polish, Swedish, Dutch, Portugese, Japanese, Simplified Chinese, Traditional Chinese, Korean, Russian, Arabic, Turkish, Finnish, Norwegian, Danish, Indonesian, Hungarian, Czech, Kazak, Vietnamese, Thai, Farsi
LAN Control- RoomView (Crestron)	Yes
LAN Control AMX Discovery	Yes
LAN Control PJ Link	Yes
H-Synch Range	15~100KHz
V-Synch Range	24~85Hz
Computer Signal Input	VGA, SVGA, XGA, SXGA,WXGA,UXGA,WUXGA
Video Signal Input	480i, 480p, 576i, 576p, 720p, 1080i and 1080p
Auto Setup	INPUT SEARCH,AUTO PC,Auto Keystone
Blank	Yes
Suspend	Yes(5 minutes no signal as default)
Picture mode	Dynamic,Standard,Cinema, Blackboard
Cooling time	0s
Closed caption	N/A
Auto Ceiling	Yes
D-Zoom	±5
	Yes
	N/A
3D	Yes
Wireless display	NA
	RJ45 USB-B USB (Type A) only support 5V Wired Remote(OUT) Speaker  Power Requeirements Power Consumption (Normal) (Max) Power Consumption (ECO1) (Max) Power Consumption (ECO2) (Max) ECO Standby Mode Power Consumption Operating Temp.  Operating Thumidity. Store Temp. High altitude  Keystone Correction (Lens@center)  Languages  LAN Control-RoomView (Crestron)  LAN Control-PJ Link H-Synch Range V-Synch Range Computer Signal Input Video Signal Input Auto Setup Blank Suspend Picture mode Cooling time Closed caption Auto Ceiling D-Zoom 360° projection Edge Blending 3D

+8613866663080

zero@yeoan.com

projector-hd.com

No. 79 Kexue Avenue, Keyuan Pioneer Center, High-tech Zone, Hefei City, Anhui Province.